



Battery Powered Photoelectric Smoke Alarm

Part Number 440378

Model P9050

One Button Design

Operates Hush™ and Test

Red LED

Flashes every 30-40 seconds to indicate that the smoke alarm is operating

Photoelectric Sensor

Advanced photoelectric sensor may detect visible particles (associated with smoldering fires) sooner than ionization alarms



Description

The Kidde P9050 is a battery operated smoke alarm, equipped with a photoelectric sensor, designed to alert you and your family to the dangers of smoke and fire.

The P9050 includes a 9V battery, providing you protection even during a power failure. This unit is UL Listed and offers a 10-year limited warranty.

This alarm uses photoelectric sensing technology. Photoelectric sensing alarms may detect visible particles (associated with smoldering fires) sooner than ionization alarms. Ionization sensing alarms may detect invisible fire particles (associated with flaming fires) sooner than photoelectric alarms.

Kidde strongly recommends that both ionization and photoelectric smoke alarms be installed to help insure maximum detection of the various types of fire that can occur within the home.

The Kidde P9050 photoelectric smoke alarm is battery operated protecting you and your family even during power outages. This unit does not require any wiring and can be installed in minutes. The P9050 is equipped with a test button that allows you to test the alarm's electronic circuitry, horn and battery function.


Features and Benefits

- **Photoelectric Sensor** – Advanced photoelectric sensor may detect visible particles (associated with smoldering fires) sooner than ionization alarms
- **Test Button** – Tests unit's electronic circuitry, horn and battery function.
- **Battery Operated (9V Battery Included)** – Protects even during a power outage.
- **Low Battery Indicator** – Smoke alarm will chirp in the event of a low battery.
- **Tamper Resist Locking Pin** – Helps deter alarm tampering or theft.



Technical Specifications

| | |
|--------------------|-------------------------------|
| UPC: | 0-47871-40378-3 |
| Power Source: | 9V Battery (included) |
| Audio Alarm: | 85dB at 10ft |
| Temperature Range: | 40°F to 100°F (4°C to 38°C) |
| Humidity Range: | 5%-95% relative humidity (RH) |
| Sensor: | Photoelectric |
| Size: | 5" in diameter x 1.5" depth |
| Weight: | .8lbs |
| Interconnects: | No |
| LED: | Red, normal operation |
| Warranty: | 10 year limited |



Ordering Information

Clamshell UPC: 0-47871-40378-3

| Part Number | I 2 of 5 | Pack Quantity | Dimensions (w x d x h inches) | Weight | Case/Skid | Layers/Skid | Skid Weight |
|-------------|-------------------|------------------------|--------------------------------|--------|-----------|-------------|-------------|
| 440378** | N/A | Individual | 7.5 x 1.87 x 11.25 | 1lb | N/A | N/A | N/A |
| 44037802 | 100 47871 40378 0 | PDQ (3 units) | 7.75 x 6 x 11.75 | 1lb | 105 | 3 | 315lbs |
| 440378-020 | 200 47871 40378 7 | Cut Case (20 units) | 16 x 20.75 x 11.75 | 20lbs | 18 | 3 | 360lbs |
| 440378-060 | 300 47871 40378 4 | Power Tower (60 units) | 20 x 24 x 39.25 (incl. pallet) | 60lbs | 3 | 3 | 180lbs |

**Not for sale by individual unit



1016 Corporate Park Drive
Mebane NC 27302
1-800-880-6788
www.kidde.com

Distributed by: