




## FIRE ALARM DETECTOR

### Manual Call Point



- **Model** : CL-201
- **Operating Power** : 24V DC 30mA
- **Operating Contact** : Max.30V DC 500mA
- **Sub-Function** : Phone Jack, confirmation LED, reset button.
- **Material** : Fire-proof plastic
- **Dimensions** : 140mm(Dia.) x 45mm(H)
- **Weight** : About 160 g



### Manual Base

CL-201



- **Model** : CL-203
- **Material** : Plastic
- **Color** : Red
- **Size** : 140 mm. x 50 mm.

CL-203




### Alarm Siren / Strobe



CL-207L

- **Model** : CL-207L
- **Input Voltage Range** : 24V DC (12 ~ 30V DC)
- **Operation Current** : LED : 50 mA (Max : 65mA)
- **Strobe** : OVER 8,000m cd. (6pcs Super bright LED)
- **Sound Output** : 100 +- 5dB (at 24V DC)
- **Tone Type** : ALARM SIREN (CL-207L)
- **Operation Temperature** : -10° C~ + 60° C
- **Continue Operation Test (at 24V DC)** : OVER 72 Hours
- **Life Test** : "ON" 1 minute, "OFF" 30 seconds, Duty Cycle (at 24V DC) Continuously over 500 Hours period
- **Color** : Red

### Fire Alarm Bell 6"



- **Model** : CL-406
- **Input Voltage** : 24V DC
- **Operation Current** : 25 mA
- **Sound Output** : 93dB@1M
- **Movement** : Motor, Pinion and Striker
- **Movement Features** : DC Motor, acetal gear wheel, steel striker
- **Gong** : Steel, secured with phillips screw
- **Base Plate** : Molded black polycarbonate
- **Color** : Red
- **Material** : Steel plate
- **Dimension** : Ø 6" (152mm) x 56mm(H)
- **Weight** : About 850g



CL-406