

QA Series



QA01
Addressable Photoelectric
Smoke Detector



QA05
Addressable Combination
Smoke & Heat Detector



QA06
Addressable Heat Detector

Addressable Detectors

Characteristics

- Address coding by dip switch makes the job easier.
- Latching function helps to identify alarm device clearly and quickly.
- Magnetic test feature makes maintenance easy and simple.
- Non-loosening screws on base terminal for easy installation.
- Detector is made of high endurance, solid and colorfast Fire-proof plastic.
- Detector has passed strict EMC test, which greatly eliminates false alarms caused by interference from nearby sources.
- Dual LEDs for 360-degree visibility.

Specifications

Model	QA01	QA05	QA06
Address Coding		Binary	
Alarm Current		DC 26V 6mA	
Standby Current		DC 26V 850µA	
Sensitivity Setting		Comply to EN54	
Ambient Temperature		0°C ~ +50°C	
Thermal Setting	N/A	58°C	58°C
Dimensions(mm)	102(Dia.) x 48(H)	102(Dia.) x 54(H)	102(Dia.) x 46(H)
Weight	130g	130g	115g
Material		Fire-proof plastic	
Color		White	

Agent In Thailand : U.P.TECH CORPORATION CO.,LTD

28 Soi Rattana Thibet 28 Yaek 2 Bangkrasor Muangnonthaburi
Nonthaburi 11000 Thailand

LINE : 0863133492 **Tel** : 02-965-7701-6, 086-355-6781

Email : sales@up-t.com **Email** : admin@up-t.com

Website : www.alarmthailand.com , www.firealarmonline.com

 **HORING LIH INDUSTRIAL CO., LTD.**

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, **Taiwan**

Tel : +886 2 22487599 **Fax** : +886 2 22407752 **Email** : export@horinglih.com **Website** : www.horinglih.com